BIG BIKE PARTS [*]		INSTALLATION INSTRUCTIONS				
Copyright [©] 2022 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written		PART NO. 41-420/4	PART NO. 41-420/41-420RED		PASSENGER BACKREST MOUNT	
permission of Big Bike Parts, Inc. 3/31/2022		FITMENT:	CAN-AM RYKER 2019-NEWER W PASSENGER SEAT		AAX MOUNT AND	
TOOLS NEEDED:	T20 TORX	PHILLIPS SCREWDRIVER	5MM ALLEN WRE		4MM ALLEN WRENCH	
	3MM ALLEN WRENCH	REMOVABLE THREAD LOCK				
TOOLS NEEDED:	3MM ALLEN WRENCH OUGH AND UNDERSTAND TH LLATION TIME: 15 TO 30 MIN IF YOU HAVE A DRIVER BA INSTALL. REMOVE THE PASSENGER BE REMOVE THE PASSENGER SE REMOVE THE PASSENGER SE REMOVE THE PASSENGER SUPPLIED IN THE KIT ACCO MAY CAUSE DAMAGE TO RE-INSTALL THE PASSENG INSTALL THE REMAINING INSTALL THE REMAINING FIG. 1 FIG. 1 MAX MOUNT, SEAR FENDER	PHILLIPS SCREWDRIVER REMOVABLE THREAD LOCK IESE INSTRUCTIONS BEFORE BEG ACKREST INSTALLED, IT MAY NEE SEAT FROM THE MAX MOUNT E SAT UPSIDE DOWN ON A CLEAN S VS AND REAR TRIM FROM THE PA BACKREST MOUNT FROM THE P DRDING TO FIG. 3. (NOTE: DO NO THE PASSENGER SEAT)	PASSENGER SMM ALLEN WRE SMM ALLEN	SEAT YI16" WRENCH Y/16" WRENCH VOABLE THREAD LOCK ON ALL FAST COVABLE THREAD LOCK ON ALL FAST ENOUGH TO REMOVE PASSENGER S COKING TAB AND SLIDING THE SEAT OCKING TO FIG. 4. OCKING TO	4MM ALLEN WRENCH TENERS* EAT) BEFORE STARTING THIS FORWARD AND UP OFF THE MAX USED) READ FORMING SCREWS TERTIGHTEN THE SCREWS OR IT VERSE STEP 2). WE X 15MM SCREW HEADJUSTMENT	
	BACKREST PAD BACKREST BACKREST	(SI®" THREAD MING SCREW (2X)		ADJUST THE BA POINT. FLIP T MORE ADJ	ACKREST STOP ACKREST STOP JUSTMENT.	
	MUDICAL BRACKET 19-32 X 107 SCREW 19-32 X 107 SCREW 19-32 X 107 SCREW 19-32 X 107 SCREW	INSTALLATION				
	ADJUSTING BRACKKET ADJUSTABLE TONGUE ItA20 X3" SCREW	ALWAYS MAKE SUF	OPERATING VEHIC	IGNORING THE C INSTRUCTIONS MAY ATES PERFORMANCE AN ION FOLLOWING THESE IN LE. DAMAGE TO THE PRO	TICE CONTENTS OF THESE AFFECT THE PRODUCT D FUNCTIONALITY. NOT NSTRUCTION MAY CAUSE ODUCT OR THE VEHICLE BEING ATTACHED.	