

INSTALLATION INSTRUCTIONS

COMFORT FRONT SHIFT LEVER FOR INDIAN®

5416 CHROME, 5417 GLOSS BLACK

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Shift Lever

YOU WILL ALSO NEED:

Metric hex socket and bit set, ft-lbs (Nm) and in-lbs (Nm) torque wrenches, blue loctite

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

- STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.
- STEP 2** Refer to PIC 2. Remove the existing shift linkage bolt that attaches the shift lever to the shift linkage. Set hardware aside, it will be reused.
- STEP 3** Refer to PIC 2. Remove mounting bolts for floorboard support, and remove the whole floorboard assembly from the bike. Set mounting hardware off to the side, it will be reused.
- STEP 4** Refer to PIC 3. Remove existing shift lever from the floorboard assembly's pivot shaft. Pay attention to the order of hardware that is removed: snap ring, flat washer, and shift lever. Leave the wave washer on the shaft. Set hardware aside, it will be reused.
- Note: If applicable remove existing heel shifter from shift lever assemble. Set the heel shifter and fasteners aside for re-installation later.*
- STEP 5** If desired, remove foot peg from existing shift lever for reuse. Set it aside until later.
- STEP 6** Locate provided Shift Lever.
- STEP 7** Refer to PIC 4. Locate the hardware that was removed in Step 4. Be sure the OEM wave washer is on the pivot shaft on the floorboard support. Place the Shift Lever followed by the flat washer onto the shaft. Secure parts in place with the snap ring.

Note: If applicable re-install the existing heel shifter, removed in Step 4, to the new shift lever.



PIC 1



PIC 3



PIC 4

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM
454 COUNTY ROAD VV SOMERSET, WI 54025

INSTALLATION INSTRUCTIONS

COMFORT FRONT SHIFT LEVER FOR INDIAN®

-CONTINUED-

STEP 8 Refer to PIC 5. Locate the floorboard support mounting hardware that was removed in Step 3. Apply a small amount of blue loctite to each bolt. Align and fasten the floorboard support to the motorcycle. Fully tighten hardware.

TORQUE VALUE FOR FLOORBOARD MOUNTING HARDWARE:
35 FT-LBS (47.5 NM)

STEP 9 Locate hardware removed in Step 2. Apply a small amount of blue loctite to the bolt. Align and fasten new shift lever with shift linkage using the shift linkage bolt.

TORQUE VALUE FOR SHIFT LINKAGE BOLT:
84 IN-LBS (9.5 NM)

STEP 10 Locate OEM or sold separately shift peg. Attach shift peg to shift lever in the reverse order of how it was removed, or via the instructions provided with the new peg.

STEP 11 Test for proper shifting functions and inspect for any possible interference. Familiarize yourself with this new location before operating the bike on public roadways.

Note: The shift linkage rod may need to be adjusted to make sure the shift lever's height is set to your desired position. Refer to your service manual for additional assistance on adjusting the shift linkage rod.

WARNING

ENSURE THAT THE INSTALLATION OF THIS PRODUCT DOES NOT INTERFERE WITH THE PROPER OPERATION OF THE MOTORCYCLE BEFORE RIDING.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.





INSTALLATION INSTRUCTIONS

COMFORT FRONT SHIFT LEVER FOR INDIAN®

-CONTINUED-

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice

KURYAKYN.COM

866 277 9598 | INFO@KURYAKYN.COM
454 COUNTY ROAD VV SOMERSET, WI 54025

