

## INSTALLATION INSTRUCTIONS

SIGNATURE SERIES VANTAGE AIR CLEANER BY JOHN SHOPE, SATIN BLACK

9271

### THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

**WARNING** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**CAUTION** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

**NOTICE** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

### ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>1 Air Cleaner Assembly, containing:                             <ul style="list-style-type: none"> <li>1 Cover</li> <li>1 Pressure Plate</li> <li>1 Air Filter</li> <li>1 Back Plate</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li>1 Hardware Kit, containing:                             <ul style="list-style-type: none"> <li>2 M5 X .8 X 12MM Socket Head Cap Screw (SHCS)</li> <li>2 M5 X .8 X 10MM Socket Head Cap Screw (SHCS)</li> <li>2 M5 X .8 X 12MM Button Head Cap Screw (BHCS)</li> <li>3 M4 X .7 X 8MM Flat Head Cap Screw (FHCS)</li> <li>1 Alcohol Pad</li> <li>1 Cord Seal Plate</li> <li>1 Foam Tube</li> </ul> </li> </ul> |
|--|---|

### YOU WILL ALSO NEED:

Metric Hex Keys, Metric Hex Bit Sockets, In-lbs (Nm) Torque Wrench, Blue Loctite

PICTURES SHOWN ARE OF THE CHROME PARTS. INSTALLATION OF THE BLACK PARTS WILL BE THE SAME.

**NOTICE** THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

**STEP 2** Refer to PIC 1. Locate Air Cleaner Assembly. Dismantle assembly, and set all the pieces aside on a flat clean surface.



## INSTALLATION INSTRUCTIONS

SIGNATURE SERIES VANTAGE AIR CLEANER BY JOHN SHOPE, SATIN BLACK

9271

-CONTINUED-

**STEP 3** Refer to PIC 2 and 3. Remove the existing air intake system; cover, retainer plate, throttle body, air box assembly, air box connector, and all fasteners. Set throttle body, mounting hardware, and throttle body o-rings aside as they will be reused.

*Note: Refer to service manual for assistance.*


**STEP 4** Refer to PIC 4 and 5. Locate AC Back Plate. Locate the two (2) stock O-Rings that were removed in Step 3. Place the O-Rings around the hole where the throttle body will re-connect, one on the front (inside) and one on the back (outside) of the plate.

**STEP 5** Refer to PIC 6 through 8. Align and connect the AC Back Plate with the breather hose. Feed the wiring harness through the hole in the lower rear corner of the back plate.

*Note: Lightly fasten the back plate to the motorcycle by using one of the OEM screws removed from the throttle body to help hold the back plate in place.*

**STEP 6** Refer to PIC 9. Locate foam tube. Wrap the foam tube around the wire harness. Place the foam wrapped wire in the gap located in the lower right corner of where the wire is feed through the back plate.

**STEP 7** Refer to PIC 10. Locate Cord Seal Plate and three (3) M4 x .7 x 8mm Flat Head Screws. Align and fasten seal plate to the lower rear corner of the back plate. Fully tighten hardware.



## INSTALLATION INSTRUCTIONS

SIGNATURE SERIES VANTAGE AIR CLEANER BY JOHN SHOPE, SATIN BLACK

9271

-CONTINUED-

**STEP 8** *Note: If you used an OEM screw to hold the back plate in place, remove it and use it for the reattachment of the throttle body in this step.*

Refer to PIC 11. Locate throttle body and mounting hardware that was removed in Step 3. Apply a small amount of blue loctite to each screw. Align and fasten the throttle body to the motorcycle. Fully tighten hardware.

**TORQUE VALUE FOR THROTTLE BODY SCREWS:**  
88.5 IN-LBS (119.99NM)



**STEP 9** Refer to PIC 12. Connect the wire harness to the throttle body, and clip-in the wire to the clamp located on the lower right corner of the throttle body.

**STEP 10** Refer to PIC 13. Locate K&N Filter. Align and place filter over the throttle body; the filter should sit on the inside edge of the back plate.

**STEP 11** Refer to PIC 14. Locate the Pressure Plate, two (2) M5 x .8 x 12mm Socket Head Cap Screws, and two (2) M8 x .8 x 10mm Flat Head Cap Screw. Align the fastening holes of the Pressure Plate with the Back Plate. Use the two M5 Socket Screws on the left (front) side of the pressure plate, and the two M5 Flat Screws on the right (rear) side of the pressure plate. Fully tighten hardware.

**STEP 12** Refer to PIC 15 through 17. Locate the Air Cleaner Cover and two (2) M5 x .8 x 12mm Button Head Cap Screws. Align the cover over the air cleaner assembly. Use the two M5 Button Screws to fasten the AC Cover to the Pressure Plate on the left (front) side and right (rear) side.

**STEP 13** Reinstall main fuse.



## INSTALLATION INSTRUCTIONS

SIGNATURE SERIES VANTAGE AIR CLEANER BY JOHN SHOPE, SATIN BLACK

9271

-CONTINUED-

### NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



FINAL

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

### RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at [www.kuryakyn.com/legal-notice](http://www.kuryakyn.com/legal-notice).

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at [www.kuryakyn.com/legal-notice](http://www.kuryakyn.com/legal-notice)

**KURYAKYN.COM**

866 277 9598 | [INFO@KURYAKYN.COM](mailto:INFO@KURYAKYN.COM)

454 COUNTY ROAD VV SOMERSET, WI 54025

