

Copyright© 2007 by Big Bike Parts, Inc. No part of this instruction sheet may be reproduced without the written permission of Big Bike Parts, Inc.

Revised 6/9/2011

TOOLS NEEDED: DRILL 1/4" DRILL BIT MASKING TAPE 4MM ALLEN WRENCH MARKING PEN

**NOTE: WE RECOMMEND USING THREADLOCKER ON ALL HARDWARE INSTALLED.**

1. COVER THE LEGS OF THE RACK (A) WITH MASKING TAPE TO PREVENT SCRATCHING WHEN POSITIONING INTO PLACE.
2. SET THE RACK (A) ON THE TRIKE FENDER AS THE DIAGRAM SHOWS AND POSITION IT TO YOUR LIKING. MAKE SURE THAT THE LEGS OF THE RACK WILL NOT INTERFERE WITH ANYTHING IMPORTANT ON THE INSIDE OF THE FENDER.
3. LIFT THE RACK (A) SLIGHTLY OFF THE SURFACE OF THE FENDER AND PLACE SHORT STRIPS OF MASKING TAPE UNDER EACH OF THE FOUR LEGS.
4. RECHECK THE RACK POSITION AND ADJUST IF NECESSARY. USING THE MARKING PEN, OUTLINE EACH MOUNTING LEG ONTO THE MASKING TAPE. REMOVE THE RACK (A) AND MARK THE CENTERS OF EACH CIRCLE WITH THE PEN.
5. USING THE DRILL WITH THE 1/4" DRILL BIT, DRILL THE CENTERS OF EACH OF THE FOUR HOLES MAKING SURE AS TO NOT DRILL THROUGH AND HIT THE TIRE. YOU CAN EITHER REMOVE THE WHEEL OR PLACE A BLOCK OF WOOD UNDERNEATH TO PREVENT PUNCTURING THE TIRE.
6. CAREFULLY REMOVE ALL MASKING TAPE FROM THE FENDER AND THE RACK LEGS. CLEAN IF NECESSARY. ATTACH THE RACK (A) TO THE FENDER USING THE M5 BUTTON HEAD SCREWS (B), METAL WASHERS (C), RUBBER WASHERS (D), AND METAL SPACERS (E) SUPPLIED. THE RUBBER WASHERS (D) ARE PLACED ON EACH SIDE OF THE FENDER.
7. REPEAT STEPS 1-6 FOR INSTALLING THE RACK ON THE OPPOSITE SIDE OF THE BIKE.
8. REPLACE THE WHEELS IF THEY WERE REMOVED.

