

INSTALLATION INSTRUCTIONS

THROW-OVER SADDLEBAGS

5258

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

Pair	Throw-Over Saddlebags	2	Strap - Single Snap Hook with Buckle
2	Removeable Bag Liner	2	Strap - Double Snap Hook with Buckle
2	Strap - Hook & Loop with Snap Hook		

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

CAUTION

KURYAKYN IS NOT RESPONSIBLE FOR IMPROPER LOADS OR UNSAFE POSITIONING OF THE THROW-OVER SADDLEBAGS. BE SURE THE WEIGHT OF THE CONTENTS IN THE BAG DOES NOT EXCEED SAFE LIMITS. IT IS THE RIDERS RESPONSIBILITY TO DETERMINE WHAT THE SAFE LIMIT IS BASED ON THE POSITION OF THE BAG, PROPER SECURING OF THE BAG AND WEIGHT LIMITS CALLED OUT BY THE MANUFACTURER OF THE MOTORCYCLE.

WARNING

YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

WARNING

PREVENT POTENTIAL SERIOUS INJURY! ENSURE ALL SADDLEBAG FASTENERS AND STRAPS ARE SECURE BEFORE RIDING THE MOTORCYCLE.



INSTALLATION INSTRUCTIONS

THROW-OVER SADDLEBAGS

5258

-CONTINUED-

WARNING

PREVENT SERIOUS INJURIES AND/OR DEATH! NEVER EXCEED THE MANUFACTURER'S RECOMMENDED LOAD LIMITS FOR YOUR MOTORCYCLE! BE SURE THE SADDLEBAGS DO NOT COME INTO CONTACT WITH ANY MOVING PARTS. ALWAYS CHECK FOR PROPER CLEARANCE BEFORE RIDING!

MOUNTING SUGGESTIONS

- The saddlebags fit either over or under the passenger seat.
- Use the adjustable straps and the hook & loop straps to secure the saddlebags to your motorcycle. DO NOT secure the saddlebags to the swingarm or any other part that moves independently from the seat. Be sure that the straps will not become tangled in any moving parts before riding.
- The saddle strap between the tops of the saddlebags is adjustable, allowing the bags to fit many applications. Loosen the saddle strap lace, adjust and retighten as necessary to properly fit your application. Be sure that the width between the saddlebags is not so loose that a saddlebag could get caught under the fender or in the wheel. Always check for proper clearance before riding. Allow for at least 4" of clearance from exhaust pipes.
- The saddlebags are equipped with multiple steel D-rings allowing you to get the best fit for your application. Slide the steel D-rings into the elastic pockets when not in use to eliminate rattling due to vibration.



WARNING

AFTER INSTALLING THE SADDLEBAGS, BE SURE TO CHECK FOR PROPER CLEARANCE BETWEEN THE BAG AND ANY MOVING PARTS, INCLUDING THE WHEELS AND SWING ARM. NEVER PLACE THE ANCHORING STRAPS NEAR THE WHEELS OR BRAKE CALIPERS. BE SURE THE PLACEMENT OF THE SADDLEBAGS DOES NOT INTERFERE WITH SAFE OPERATION OF THE MOTORCYCLE.

NOTICE

THE SADDLEBAGS HAVE HEAT-RESISTANT SHIELDS BUT WE DO NOT RECOMMEND PLACING THE BAGS NEAR EXHAUST PIPES. BE SURE TO MAINTAIN PROPER CLEARANCE AWAY FROM EXHAUST PIPES. ALLOW AT LEAST 4" CLEARANCE FROM EXHAUST PIPE.

INSTALLATION INSTRUCTIONS

THROW-OVER SADDLEBAGS

5258

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE IS REQUIRED ON ALL FASTENERS.

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice