

INSTALLATION INSTRUCTIONS

LEGACY LEVERS FOR INDIAN® SCOUT, CHROME

7135

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

- 1 Brake Lever
- 1 Clutch Lever

YOU WILL ALSO NEED:

Flat head screw driver, socket and torque wrench

NOTICE THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool. Remove main fuse.

WARNING A FACTORY SERVICE MANUAL WILL BE HELPFUL IN PERFORMING THIS INSTALLATION. DO NOT ATTEMPT TO PERFORM THIS INSTALLATION IF YOU ARE NOT CONFIDENT IN YOUR ABILITY TO COMPLETE ALL OF THE STEPS IN THE PROCEDURE; CONSULT A TRAINED TECHNICIAN. IMPROPER INSTALLATION COULD RESULT IN SERIOUS INJURY OR DEATH.

WARNING ACCIDENTAL VEHICLE START-UP COULD CAUSE DEATH OR SERIOUS INJURY, REMOVE THE MAIN FUSE BEFORE PROCEEDING.

NOTICE AVOID DAMAGE TO THE MOTORCYCLE. PROTECT PAINTED SURFACES WITH A SOFT CLOTH OR BLANKET.


BRAKE SIDE

STEP 2 Refer to PIC 3 and 4. Carefully remove the existing nut, pivot bolt, and brake lever. Set hardware aside, it will be used later.

PIC 1



PIC 2



PIC 3



PIC 4



INSTALLATION INSTRUCTIONS

LEGACY LEVERS FOR INDIAN® SCOUT, CHROME

7135

-CONTINUED-

STEP 3 Refer to PIC 5 and 6. Be sure the bushing is properly placed in the provided Brake Lever. Align and place the Brake Lever into the perch. Install the pivot bolt and nut that were removed in Step 2. Tighten the screw. Hold the screw in place to tighten the nut.

Ensure that the brake switch and brake plunger are compressed as the lever is installed.

TORQUE VALUE FOR NUT: 52 IN-LBS (6.0 NM)

STEP 4 Compress the Brake Lever a few times to ensure that the brakes and brake lights work properly BEFORE starting the motorcycle.



PIC 5



PIC 6


CLUTCH SIDE

STEP 5 Refer to PIC 7. Carefully remove the existing nut and pivot bolt. Set hardware aside, it will be used later.

Loosen the clutch cable, pull the clutch lever forward (towards the front of the bike), and remove the clutch lever from its perch. Disconnect the clutch cable from the clutch lever.

Note: Refer to your motorcycle's user manual for assistance with the clutch cable.

STEP 6 Refer to PIC 8 and 9. Attach the clutch cable to the provided Clutch Lever. Align and place the provided Clutch Lever into the perch. Be sure the bushing is properly placed, the clutch cable wire is set in the slot of the perch, and the outer casing is recessed into the outside of the perch.



PIC 7



PIC 8

PIC 9

STEP 7 Refer to PIC 10. Install the pivot bolt and nut that were removed in Step 5. Be sure pivot bolt is properly seated. Tighten the nut.

Ensure that the clutch switch and clutch plunger are compressed as the lever is installed.

TORQUE VALUE FOR NUT: 52 IN-LBS (6.0 NM)

INSTALLATION INSTRUCTIONS

LEGACY LEVERS FOR INDIAN® SCOUT, CHROME

7135

-CONTINUED-

- STEP 8** Compress the Clutch Lever a few times to ensure that the clutch work properly BEFORE starting the motorcycle. Adjust clutch cable freeplay if necessary.

Note: Refer to your motorcycle's user manual for assistance with the clutch cable free play adjustments.

PIC 10

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.



LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice